



7400A TerrainCut™

Key Specs

Maximum Engine Power - 2600.0 rpm

Maximum Engine Power - 27.7 kW

Drive Pump - Gear

Ground Pressure - 96.5 kPa

Throttle - Hand throttle at operator's right on command arm

Operator Display - TechControl Display; Located on Command Arm; displays machine warnings, on-board electrical diagnostics; service timers on large easy to read screen; quick on the go settings for mow and transport speed; Turn Speed; Loadmatch™ and ON/OFF Cruise Control Use selection: all settings are pass code protected

Ground Speed - Mowing - 10.0 km/h

Cutting Width - 188.0 cm

Height-Of-Cut - No tool adjustment: 2.54-10.2 cm (1-4 in.)

Reel Diameter - 17.8 cm

Engine

Type - Direct Inject Turbocharged Diesel

Engine Type - Direct Inject Turbocharged Diesel

Compliant Emission Regulation - Interim Tier 4

Maximum Engine Power - 2600.0 rpm

Maximum Engine Power - 27.7 kW

Cylinders - 3

Displacement - 1.568 L

Air Cleaner - 2-stage dry element

Fuel - Diesel

Engine

Cooling System - Liquid centrifugal pump; forward machine location for optimum cooling

Vehicle

Drive Pump - Gear

Hydraulic System Capacity - 45.4 L

Fuel Tank Capacity - 45.4 L

Steering - Hydraulic power with double acting steering cylinder

Front Drive Tires - 24 x 12 - 12 turf trac

Steering Tires - 24 x 12 - 12 multi trac

Ground Pressure - 96.5 kPa

Brakes - Internal hydraulic wet disc brakes with dynamic braking through closed loop hydrostatic system

ROPS - Standard; meets ISO 21299 standards

Operating Weight

Cutting Units Lowered - 1216.0 kg

Controls

Throttle - Hand throttle at operator's right on command arm

Forward/Reverse - Dual pedal

Mower Lift - One-touch single handle

Parking Brake - Electric Switch on Command Arm for Internal Wet Disk Brakes

Seat - Suspension seat with seat belts and arm rest; fore/aft adjustment; weight and lumbar adjustment

PTO - Electric Switch on Command Arm

Ignition - Key start

Work Lights - Switch on Command Arm

Tilt Steering - Left Foot operated for easy adjustment

Operator Display - TechControl Display; Located on Command Arm; displays machine warnings, on-board electrical diagnostics; service timers on large easy to read screen; quick on the go settings for mow and transport speed; Turn Speed; Loadmatch™ and ON/OFF Cruise Control Use selection: all settings are pass code protected

Storage - Cup holder; two-way radio; large operator storage located on left hand side of operator station

Dimensions

Height With ROPS - 213.4 cm

Length - 338.0 cm

Transport Width - 194.3 cm

Dimensions

Mowing Position Width - 188.0 cm

Ground Speed - Mowing - 10.0 km/h

Ground Speed - Transport - 14.0 km/h

Ground Speed - Reverse - 6.4 km/h

Cutting Units

Number - 3

Cutting Unit Size - 68.6 cm

Cutting Width - 188.0 cm

Height-Of-Cut - No tool adjustment: 2.54-10.2 cm (1-4 in.)

Reel Diameter - 17.8 cm

Bedknife Adjustment - Reel-to-bedknife

Backlapping - Standard

Sound Levels

Operator Ear Full Engine RPM - 90.0 dBA

Measuring Standard - ISO 11201, EN ISO5395-1

Attachments Installed - FTCs, reels engaged

Fuel Economy

Actual Fuel Usage Will Vary Depending On Course Conditions, Operation, Turf And Fuel Quality - 2.88 L/hr

Warranty

Type - Two-year limited

Certification

Type - ANSI B71.4-2012, CE