



TruFinish™ 1220

### Key Specs

Engine Type - Air-cooled

Displacement - 570.0 cc

Horsepower - 13.4 kW

Tank Capacity - 18.9 L

Transmission Type - Hydrostatic with 3 hydraulic wheel motors and selectable 2WD/3WD

Travel Speed - Forward - 19.0 km/h

Travel Speed - Reverse - 6.0 km/h

Ground Clearance At Rake Attachment - 139 - 178 mm

### Engine

Manufacturer - Air-cooled

Engine Type - Air-cooled

Displacement - 570.0 cc

Horsepower - 13.4 kW

Lubrication - Full-pressure

Oil Capacity - 1.4 L

Oil Filter - Standard

Idle Speed - Low Speed - 1,750 rpm

Idle Speed - Fast Speed - 3,300 rpm

### Electrical System

Type - 12 V

## Electrical System

Battery - 300 CCA 12 V V

Starter - Electric

Ignition - Transistor-type

Light Kit - Available

## Fuel System

Tank Capacity - 18.9 L

Fuel Required - Unleaded gasoline

## Transmission

Transmission Type - Hydrostatic with 3 hydraulic wheel motors and selectable 2WD/3WD

Fluid Capacity - 18.9 L

## Travel Speed

Travel Speed - Forward - 19.0 km/h

Travel Speed - Reverse - 6.0 km/h

## Brakes

Type - Dual rear wheel parking brakes; dynamic braking provided by closed loop hydrostatic powertrain

## Tires

Front - One 22-11x10 Knobby Tire kPa

Rear - Two 22-11x10 Knobby Tire kPa

## Dimensions

Width - 1470.0 mm

Height - 1890.0 mm

Length - 1730.0 mm

Wheelbase - 1070.0 mm

Ground Clearance At Rake Attachment - 139 - 178 mm

Weight (Approx.) - 431.0 kg