



Z955R

## Key Specs

Engine Manufacturer/Model - FX781V EVO EFI

Engine Power - CE nominal power and speed 19.1 kW 25.6 hp at 3200 rpm

Fuel Tank Capacity - 43.5 L

Transmission - Hydrostatic

Speed Range - 16.9 km/h

Drive Wheels - 24x12-12 (optional Tweel)

Mower Deck Size - 137-cm (54-in.) 7Iron™ PRO side-discharge 152-cm (60-in.) 7Iron™ PRO side-discharge  
152-cm (60-in.) FastBack™ PRO rear-discharge

Caster Wheels - 13x6.5-6

## Engine

Engine Manufacturer/Model - FX781V EVO EFI

Engine Power - CE nominal power and speed 19.1 kW 25.6 hp at 3200 rpm

Displacement - 822.0 cc

Cylinders - 2

Crankcase Capacity - 2.1 L

Oil Filter - Full flow, replaceable

Lubrication - Full pressure

Cooling - Forced air, with integrated clean out ports and oil cooler

Air Cleaner - Heavy-duty canister type with safety element

Pre-Cleaner - Yes

## Fuel System

## Fuel System

Fuel Type - Gasoline

Fuel Tank Capacity - 43.5 L

Fuel Tank Switch/Shut-Off Valve - No

## Electrical System

Charge System - 30.0 amp

Battery Voltage - 12.0 V

Hour Meter - Display panel including hour meter, fuel level, engine speed, system voltage, low engine oil pressure indicator, starting interlock indicators (PTO, operator presence, park brake), caution warning, stop warning, and on-board diagnostics

Operator Presence Starting System - Standard

## Drivetrain

Transmission - Hydrostatic

Wheel Motors - Tuff Torq heavy-duty integrated piston wheel motor with cross porting

Speed Range - 16.9 km/h

Forward Speed - 16.9 km/h

Reverse Speed - 6.4 km/h

Speed Direction And Control - Twin levers

Hydraulic Capacity - 5.6 L

Filter - Internal, replaceable

## Tires

Drive Wheels - 24x12-12 (optional Tweel)

Load Rating - 4 PR

## Brakes

Dynamic Braking - Twin levers

Park Brake - Internal wet disk integrated in the transmission

Park Brake Actuation - Foot brake

## PTO

Type - Electromagnetic: 305 Nm 225 lb-ft

Drive - V-belt

## Mower Decks

Mower Deck Size - 137-cm (54-in.) 7Iron™ PRO side-discharge 152-cm (60-in.) 7Iron™ PRO side-discharge  
152-cm (60-in.) FastBack™ PRO rear-discharge

Deck Construction - 7-Iron™ PRO: 7-gauge, 4.6-mm (0.179-in.) one-piece forged steel FastBack™ PRO:  
7-gauge, 4.6-mm (0.179-in.) fabricated steel

Deck Thickness - 7 gauge 4.6 mm 0.18 in.

Height-Of-Cut Range - 2.54-14 cm

Increments - 0.64 cm

Cutting Width - 137 or 152 cm

## Blades

Length - Varies by deck size

Thickness - 7Iron PRO: 0.25 in. 6.4 mm FastBack PRO: 0.31 in. 8 mm

Number - 3

## Wheels

Caster Wheel Type - Flat free

Caster Wheels - 13x6.5-6

Front Anti-Scalp Rollers - Left, center, right

Rear Anti-Scalp Rollers - 7Iron PRO: Left, center, right FastBack PRO: Left, right

## Dimensions

Length - 221 cm 87 in.

Width - With Chute Down - 188.0 cm

Width - Rear Discharge - 161.3 cm

Height - With ROPS Up - 185.0 cm

Height - With ROPS Down - 119.0 cm

Weight - 681 kg

## Additional Information

Date Collected - 2024-12-01T17:35:00