



1026R

Key Specs

Engine Make - Yanmar®

Engine Model - 3TNV76-XCJT

Displacement - 68 cu in

Rated Engine Power - 18 kW

Rated Engine Power - 25 PS

Maximum Engine Power - 18 kW

Maximum Engine Power - 25 PS

Transmission Type - Hydrostatic transmission 2F/2R

Rear Hitch Category (SAE Designation) - Category 1

Pump Rated Output - 13.2 L/min

Base Machine Weight - 928 kg

Machine Configuration

Wheel or Track Configuration - Wheel

Drive Type - 4WD

Engine

Engine Make - Yanmar®

Engine Model - 3TNV76-XCJT

Emissions Certifications - Stage V

Displacement - 68 cu in

Aspiration - Natural

Engine

Number of Cylinders - 3

Cylinder Liners - Cast-in-block

Rated Engine Speed - 3200 rpm

Rated Engine Power - 18 kW

Rated Engine Power - 25 PS

Rated Engine Power with IPM - 40 kW

Rated Engine Power with IPM - 55 PS

Maximum Engine Power - 18 kW

Maximum Engine Power - 25 PS

Bore and Stroke - 76 x 82 mm

Compression Ratio - 23.5:1

Lubrication - Pressurized

Cooling System Type - Liquid

Fuel Type - Diesel

Air Cleaner Type - Dry type with safety element

Transmission

Transmission Type - Hydrostatic transmission 2F/2R

Reverser - No

Clutch - Wet disk

Cruise Control - Optional

Rear Power Take-Off (PTO)

Rated PTO Power - 12 kW

PTO Clutch - Wet disk

Brake (For Mid and Rear PTO) - Wet disk

Rear Hitch

Rear Hitch Category (SAE Designation) - Category 1

Lift Capacity Through Full Lift Range at 610-mm Behind Hitch Point - 344

Hydraulics

Hydraulic System Type - Open center

Pump Rated Output - 13.2 L/min

Hydraulics

Maximum Operating Pressure - 138 bar

Front Axle

Front Axle Differential Lock - Yes

Rear Axle

Rear Differential Lock - Yes

Final Drive - Spur gear

Steering & Brakes

Steering Type - Power steering

Primary Brakes - Wet disk

Electrical System

Battery Cold Cranking Amps - 500 CCA

Alternator Capacity - 55 amp

Operator Station

ROPS Type - Fixed

Capacities

Fuel Tank Capacity - 23.96 L

Transmission - Hydraulic System - 12.3 L

Crankcase Oil Volume - 2.7 L

Dimensions & Weights

Wheelbase - 1450 mm

Base Machine Weight - 928 kg

Ground Clearance - 223 mm