



2032R

Key Specs

Engine Make - Yanmar®

Displacement - 1 cu in

Rated Engine Power - 23 kW

Rated Engine Power - 31 PS

Maximum Engine Power - 23 kW

Maximum Engine Power - 31 PS

Transmission Type - Hydrostatic transmission Infinite/two-range

Rear Hitch Category (SAE Designation) - Category 1

Base Machine Weight - 1127 kg

Machine Configuration

Wheel or Track Configuration - Wheel

Drive Type - 4WD

Engine

Engine Make - Yanmar®

Emissions Certifications - Stage V, FT4

Displacement - 1 cu in

Aspiration - Natural

Number of Cylinders - 3

Cylinder Liners - Cast-in-block

Rated Engine Speed - 2500 rpm

Engine

Rated Engine Power - 23 kW

Rated Engine Power - 31 PS

Engine Torque at Rated Speed - 88 Nm

Maximum Engine Power - 23 kW

Maximum Engine Power - 31 PS

Maximum Engine Torque - At 1600 rpm: 1732 Nm 1277 lb-ft

Bore and Stroke - 88 x 90 mm

Compression Ratio - 19.1:1

Lubrication - Pressurized

Cooling System Type - Liquid

Fuel Type - Diesel

Air Cleaner Type - Dry type with safety element

Transmission

Transmission Type - Hydrostatic transmission Infinite/two-range

Creeper - No

Reverser - No

Clutch - Wet

Cruise Control - Yes

Rear Power Take-Off (PTO)

Rated PTO Power - 18 kW

Engagement Method - Independent

PTO Clutch - Wet

Rear Hitch

Rear Hitch Category (SAE Designation) - Category 1

Hydraulics

Hydraulic System Type - Open center

Maximum Operating Pressure - 172 bar

Rear Axle

Rear Differential Lock - Yes

Rear Axle

Final Drive - Spur gear

Steering & Brakes

Steering Type - Power steering

Primary Brakes - Wet

Electrical System

Battery Cold Cranking Amps - 500 CCA

Operator Station

ROPS Type - Fixed

Capacities

Fuel Tank Capacity - 32.5 L

Transmission - Hydraulic System - 24.8 L

Crankcase Oil Volume - 4.5 L

Dimensions & Weights

Wheelbase - 1725 mm

Base Machine Weight - 1127 kg

Front Axle Ground Clearance - 305 mm