



4066M

Key Specs

Engine Make - Yanmar®

Displacement - 179 cu in

Rated Engine Power - 48 kW

Rated Engine Power - 65 PS

Maximum Engine Power - 48 kW

Maximum Engine Power - 65 PS

Transmission Type - Hydrostatic transmission 3F/3R

Rear Hitch Category (SAE Designation) - Category 1

Base Machine Weight - 1774 kg

Machine Configuration

Wheel or Track Configuration - Wheel

Drive Type - 4WD

Engine

Engine Make - Yanmar®

Emissions Certifications - Stage V

Displacement - 179 cu in

Aspiration - Turbocharged and intercooled

Number of Cylinders - 4

Cylinder Liners - Cast-in-block

Rated Engine Speed - 2600 rpm

Engine

Rated Engine Power - 48 kW

Rated Engine Power - 65 PS

Engine Torque at Rated Speed - 178 Nm

Maximum Engine Power - 48 kW

Maximum Engine Power - 65 PS

Bore and Stroke - 88x90 mm

Compression Ratio - 19.1:1

Lubrication - Pressurized

Cooling System Type - Liquid

Fuel Type - Diesel

Air Cleaner Type - Dry type with safety element

Transmission

Transmission Type - Hydrostatic transmission 3F/3R

Reverser - No

Clutch - Wet disk

Cruise Control - Cab only

Rear Power Take-Off (PTO)

Rated PTO Power - 39 kW

Engagement Method - Independent

PTO Clutch - Wet disk

Brake (For Mid and Rear PTO) - Wet disk

Rear Hitch

Rear Hitch Category (SAE Designation) - Category 1

Maximum Lift Capacity at 610-mm Behind Hitch Point - 2709.5 lb 1229 kg

Hydraulics

Hydraulic System Type - Open center

Maximum Operating Pressure - 172 bar

Rear Axle

Rear Differential Lock - Yes

Rear Axle

Final Drive - Planetary

Steering & Brakes

Steering Type - Power-assisted

Primary Brakes - Wet disk

Electrical System

Battery Cold Cranking Amps - 500 CCA

Alternator Capacity - 75 amp

Operator Station

ROPS Type - Fixed

Capacities

Fuel Tank Capacity - 56.9 L

Transmission - Hydraulic System - 47.3 L

Crankcase Oil Volume - 5.3 L

Dimensions & Weights

Wheelbase - 1850 mm

Base Machine Weight - 1774 kg

Front Axle Ground Clearance - 288 mm